


Orion DuraFlow & EnergySaver

NEW 4" PORTED PLATE HEAT EXCHANGER

The new 4" ported Orion plate exchanger from SPX is designed to cover a wide range of applications and secure even better solutions for customers in the energy, food, marine and industrial segments.

By implementing features developed over the past 10 years we can now deliver an even more cost effective heat exchanger with a superior ratio between plate thickness and pressure rating.

	FEATURE	ADVANTAGES	WHAT'S IN IT FOR YOU!
A	CORNERLOCK	SUPERIOR PLATE STACK STABILITY ENABLES THE USE OF THINNER AND MORE EFFICIENT PLATES WITHOUT COMPROMISING MECHANICAL STRENGTH.	INCREASED PRODUCTION TIME AS MAINTENANCE TIME IS REDUCED TO A MINIMUM. SERVICE CAN BE DONE EASILY BY PERSONNEL ON SITE SAVING BOTH TIME AND MONEY. LONGER LIFE TIME OF PLATE PACK.
B	GRADUATED CHOCOLATE BOX DISTRIBUTION	BETTER THERMAL PERFORMANCE OF PLATE -> REDUCTION IN M ² OF REQUIRED HEAT TRANSFER AREA AND IMPROVED PERFORMANCE	
C	EASYCLIP	IMPROVED STABILITY OF GASKET AND REDUCED RISK OF GASKET BLOWOUT.	



Frame dimensions:

FRAME	WIDTH IN MM (INCH)	HEIGHT IN MM (INCH)	CONNECTION DIAMETER MM (INCH)	DESIGN
ORION 034 MGS-10	448 (17)	1348 (53)	100 (4)	INDUSTRIAL FRAME
ORION 034 MGS-16	465 (18)	1356 (53)		
ORION 050 MGS-10	448 (17)	1809 (71)		
ORION 050 MGS-16	465 (18)	1817 (71)		
ORION 034 RKS-06	453 (18)	1580 (62)		
ORION 034 RKS-10	495 (19)	1580 (65)		SANITARY FRAME
ORION 034 RKS-25	509 (20)	1644 (65)		
ORION 050 RKS-06	453 (18)	1975 (78)		
ORION 050 RKS-10	495 (19)	1975 (78)		
ORION 050 RKS-25	509 (20)	2040 (80)		

GENERAL SPECIFICATIONS

Design:

Industrial frame, painted to RAL 5010 Blue

Sanitary frame, stainless steel

	PED	ASME
DESIGN CODE:	PRESSURE EQUIPMENT DIRECTIVE PED EN 1.3445	ASME VIII DIV1
TEMPERATURE:	0 - 150°C MAX PRESSURE: 10 AND 16 BAR	UP TO 200°C - 10 BAR AND 20 BAR UP TO 392°F - 150 PSI AND 300 PSI

Materials:

Plates: Stainless steel EN 1.4301(AISI304), EN 1.4401(AISI316) or Titanium Gr 1

Gaskets: NBR or EPDM clipped

Connections: EN 1.4401, titanium or rubberlined

TYPICAL APPLICATIONS

Food:

- Cooling/pasteurization of milk
- Whey
- Beer
- Wort

Industry:

- General heating and cooling duties

Marine:

- Water/Water
- Water/Oil

Energy:

- Hot tap water
- Central heating

SPX FLOW TECHNOLOGY

105 Crosspoint Parkway
Getzville, NY 14068
USA
P: (800) 207-2708
F: (716) 692-1715
E: answers.us@apv.com

SPX FLOW TECHNOLOGY

666 Fengjin Road, Xidu Industrial Park
Feng Xian District
ShangHai 201401
PR China
P +86 21 6715 8181
F +86 21 6715 8282

SESINOKS®

Sesinoks Metal ve End. Ürünler San.Tic. A.Ş.
Dudullu OSB 2. Cad. No: 20 Ümraniye - İSTANBUL - TR
Tel: +90 216 420 10 00 Fax : +90 216 420 74 39
www.sesinoks.com.tr info@sesinoks.com.tr

SPX®

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.spx.com.

SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

APV-1212-GB Version: 04/2011 Issued: 12/2011 COPYRIGHT © 2010, 2011 SPX Corporation

SPX Flow Technology, Platinvej 8, 6000 Kolding, Denmark

P: +45 70 278 444 F: +45 70 278 445 E: apv.emea.heat@spx.com